



RU88-DWC RU88-DWC Metal Hook

Model	RU988-DWC	RU788-DWC	RU588-DWC	RU488-DWC
Device Configurations				
Battery size	Rechargeable Lithium-Ion			
Control Options	PB and VC			
IP Classification	IP68			
Audiological Features				
Number of Channels	17	14	12	10
360 All-Around	●	-	-	-
All Access Directionality	-	●	-	-
Binaural Directionality III	-	-	●	-
Binaural Directionality	-	-	-	●
Spatial Sense	●	●	●	-
Front Focus	●	-	-	-
Ultra Focus	-	●	-	-
Synchronised Soft Switching	●	●	●	●
Environmental Optimiser II	●	-	-	-
Environmental Optimiser I	-	●	●	-
Noise Tracker II	5 settings	3 settings	2 settings	On/Off
Expansion	3 settings	2 settings	On/Off	On/Off
Impulse Noise Reduction	3 settings	3 settings	On/Off	On/Off
Wind Guard	3 settings	2 settings	On/Off	On/Off
Sound Shaper	●	●	●	●
DFS Ultra III (w/ Music Mode)	●	●	●	●
Synchronised Acceptance Manager	●	●	●	●
Tinnitus Sound Generator	●	●	●	●
Functional Features				
Ear to Ear Communication	●	●	●	●
Direct audio streaming	●	●	●	●
Direct Audio Input (DAI)	●	●	●	●
Telecoil (TC)	●	●	●	●
ReSound TV Streamer 2, Remote Control, Remote Control 2, Phone Clip+, Micro Mic and Multi Mic	●	●	●	●
ReSound Smart 3D™ app	●	●	●	●
Sound Enhancer (ReSound Smart 3D™ app)	●	●	●	●
Remote Fine Tuning and Updates				
ReSound Assist	●	●	●	●
ReSound Assist Live	●	●	●	●
Remote Firmware Updates	●	●	●	●
Fitting Features				
Fitting Software Smart Fit™ 1.16 or higher	●	●	●	●
Fully Flexible Programs	4	4	4	4
Auto DFS	●	●	●	●
Datalogging	●	●	●	●
Wireless Fitting with Noahlink Wireless	●	●	●	●



Charger




Charging cable



AC/DC Adaptor (EU example)

Technical data	Desktop Charger
Dimensions	82mm x 36mm x 46mm / 3.2" x 1.4" x 1.8"
Weight	82 grams / 2.9 oz
Power Supply	USB power supply, 5 V
Charging form factor (CFF)	80
Charging time for Hearing Instrument	< 40 °C (104F): 3 hours, depending on initial state of the battery
Wireless frequency between Hearing Instrument and Charger	2.4 GHz and 333 kHz
ESD tolerance	According to IEC 61000-4-2 Electrostatic discharge immunity test standard
Operating & Charging temperature	+ 5 °C (41F) to + 40 °C (104F) at a relative humidity range of 15% to 90%, non-condensing
Storage temperature for charger and Hearing Instrument	- 25 °C (-13F) to + 5 °C (41F), + 5 °C (41F) to + 35 °C (95F) at a relative humidity up to 90%, non-condensing, > 35 °C (95F) to 70 °C (158F) at a water vapour pressure up to 50 hPa



© 2022 GN Hearing A/S. All rights reserved. ReSound is a trademark of GN Hearing A/S. Apple, the Apple logo, iPhone, iPad and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google LLC.

Worldwide Headquarters
GN ReSound A/S
Lautrupbjerg 7
DK-2750 Ballerup
Denmark
Tel: +45 4575 1111
resound.com

United Kingdom
GN Hearing UK Ltd.
Unit 13
Talisman Business Centre
Bicester
Oxon OX26 6HR
Tel: +44 1869 352800
resound.com

Australia
GN Hearing Australia Pty Ltd
Gate C, 19-25 Khartoum Road
Macquarie Technology Park
Macquarie Park NSW 2113
Tel: (free) 1800 658 955
resound.com

New Zealand
GN Hearing New Zealand Limited
Ground Floor, North Entrance
4 Fred Thomas Drive
Takapuna, Auckland, 0622
Tel: (free) 0800 900 126
resound.com

Singapore
GN Hearing Pte. Ltd.
456 Alexandra Road
#22-01
Singapore 119962
Tel: +65 6320 9388
resound.com

Technical Specifications

		RU88-DWC		
		IEC 60118-0: 1983_ AMD1:1994 IEC 60118-0:2015 IEC 711 Ear simulator	ANSI S3.22-2014 IEC 60118-0:2015 JIS C 5512: 2015 2cc coupler	
Reference test gain (60 dB SPL input)	1600 Hz/HFA	57	52	dB
Full-on gain (50 dB SPL input)	Max. 1600 Hz/HFA	75 67	67 61	dB
Maximum output (90 dB SPL input)	Max. 1600 Hz/HFA	140 134	133 129	dB SPL
Total harmonic distortion	500 Hz 800 Hz 1600 Hz	0.7 1.3 0.4	0.7 0.6 0.3	%
Telecoil sensitivity (1 mA/m input)	Max.	105	97	dB SPL
HFA - SPLIV @ 31.6 mA/m (ANSI)	HFA	121	112	
Full-on telecoil sensitivity @ 1mA/m	1600 Hz/HFA	97	92	
Equivalent input noise, w/o Noise reduction		23	20	dB SPL
1/3 Octave Equivalent input noise, w/o Noise reduction	1600 Hz	11	10	dB SPL
Frequency range IEC60118-0:2015*		100-6440	100-5170	Hz
Battery Lifetime (Battery type Rechargeable)**		24	24	Hours

* Measured according to IEC 60118-0:2015, with 711-Ear simulator coupler.
 ** Expected operating time of the rechargeable battery depends on active features, the use of wireless accessories, hearing loss, battery age and sound environment.













Technical Specifications

		RU88-DWC - Metal hook***		
		IEC 60118-0: 1983_ AMD1:1994 IEC 60118-0:2015 IEC 711 Ear simulator	ANSI S3.22-2014 IEC 60118-0:2015 JIS C 5512: 2015 2cc coupler	
Reference test gain (60 dB SPL input)	1600 Hz/HFA	59	52	dB
Full-on gain (50 dB SPL input)	Max. 1600 Hz/HFA	80 72	73 67	dB
Maximum output (90 dB SPL input)	Max. 1600 Hz/HFA	140 134	133 129	dB SPL
Total harmonic distortion	500 Hz 800 Hz 1600 Hz	1.0 1.8 0.5	0.7 1.0 0.4	%
Telecoil sensitivity (1 mA/m input)	Max.	110	102	dB SPL
HFA - SPLIV @ 31.6 mA/m (ANSI)	HFA	122	112	
Full-on telecoil sensitivity @ 1mA/m	1600 Hz/HFA	103	97	
Equivalent input noise, w/o Noise reduction		23	20	dB SPL
1/3 Octave Equivalent input noise, w/o Noise reduction	1600 Hz	11	11	dB SPL
Frequency range IEC60118-0:2015*		100-5430	100-4970	Hz
Battery Lifetime (Battery type Rechargeable)**		24	24	Hours

* Measured according to IEC 60118-0:2015, with 711-Ear simulator coupler.
 ** Expected operating time of the rechargeable battery depends on active features, the use of wireless accessories, hearing loss, battery age and sound environment.
 *** Metal hook version of RU88-DWC models are configured in fitting software with the metal hook accessory.

Patents pending

All specifications are subject to change without notice



Patents pending

All specifications are subject to change without notice