



Model (MM Receiver)	RT961-DRW RT961-DRWC RT962-DRW	RT761-DRW RT761-DRWC RT762-DRW
Device Configurations		
Battery size 61-DRW	312 Zinc-Air	
Battery size 61-DRWC	Rechargeable Lithium-Ion	
Battery size 62-DRW	13 Zinc-Air	
Receiver Options	MM	
Control Options	PB (61-DRW and 61-DRWC), Multi-Function button (62), Telecoil (62)	
IP Classification	IP68	
Audiological Features		
Number of Channels	17	14
All Access Directionality	●	●
M&RIE	●	●
Ultra Focus	●	-
Synchronised Soft Switching	●	●
Environmental Optimiser II	●	-
Environmental Optimiser I	-	●
Noise Tracker II	5 settings	3 settings
Expansion	3 settings	2 settings
Impulse Noise Reduction	3 settings	3 settings
Wind Guard	3 settings	2 settings
DFS Ultra III (w/ Music Mode)	●	●
Synchronised Acceptance Manager	●	●
Tinnitus Sound Generator	●	●
Functional Features		
Ear to Ear Communication	●	●
Direct audio streaming	●	●
ReSound TV Streamer 2, Remote Control, Remote Control 2, Phone Clip+, Micro Mic and Multi Mic	●	●
ReSound Smart 3D™ app	●	●
Sound Enhancer (ReSound Smart 3D™ app)	●	-
ReSound Assist		
Remote Fine Tuning	●	●
Remote Firmware Updates	●	●
ReSound Assist Live	●	●
Fitting Features		
Fitting Software Smart Fit™ 1.8 or higher	●	●
Max Gain Handles	17	14
Fully Flexible Programs	4	4
Datalogging	●	●
Wireless Fitting with Noahlink Wireless	●	●
Automatic Receiver Detection	●	●



Technical Specifications


		MM		
		IEC 60118-0: 1983_AMD1:1994 IEC 60118-0:2015 IEC 711 Ear simulator	ANSI S3.22-2014 IEC 60118-0:2015 JIS C 5512: 2015 2cc coupler	
Reference test gain (60 dB SPL input)	1600 Hz/HFA	41	33	dB
Full-on gain (50 dB SPL input)	Max. 1600 Hz/HFA	63 53	53 47	dB
Maximum output (90 dB SPL input)	Max. 1600 Hz/HFA	124 117	115 110	dB SPL
Total harmonic distortion	500 Hz 800 Hz 1600 Hz	0.3 1.4 0.8	0.1 0.9 0.4	%
Telecoil sensitivity (1 mA/m input)*	Max. HFA - SPLIV @ 31.6 mA/m (ANSI)	92 103	82 93	dB SPL
Full-on telecoil sensitivity @ 1mA/m	1600 Hz/HFA	82	75	
Equivalent input noise, w/o Noise reduction		22	20	dB SPL
1/3 Octave Equivalent input noise, w/o Noise reduction	1600 Hz	7	7	dB SPL
Frequency range IEC60118-0:2015**		100-9550	100-9100	Hz
Battery Lifetime (Battery type Rechargeable)***		30	30	Hours
Current Drain (Quiescent / Operating) (Model 61-DRW, 62-DRW)		0.82 / 0.85	0.82 / 1.04	mA

* Telecoil is only for the RTx62-DRW models.
 ** Measured according to IEC 60118-0:2015, with 711-Ear simulator coupler.
 *** Expected operating time of the rechargeable battery depends on active features, the use of wireless accessories, hearing loss, battery age and sound environment.

Technical data	Premium Charger	Standard Charger
Dimensions	99.4 x 35 x 67.5 mm / 3.9 x 1.4 x 2.7"	100.2 mm x 42 mm x 54.8 mm / 3.9 x 1.7 x 2.2"
Weight	145 gram / 5.1 oz	95 gram / 3.3 oz
Power Supply	USB power supply, 5 V	USB power supply, 5 V
Internal Power Source	Rechargeable Lithium Ion battery, 3.7 V, 2600 mAh	N/A
Charging time for internal lithium ion battery in Charger	Max 3,5 hours, depending on initial state of the battery	N/A
Battery life (fully charged, not connected to mains power)	Min. 3 full charges of 2 hearing instruments, Without hearing instruments: 12 months	N/A
Charging time for Hearing Instrument	< 40 °C (104F): 3 hours, depending on initial state of the battery	< 40 °C (104F): 3 hours, depending on initial state of the battery
Wireless frequency between Hearing Instrument and Charger	2.4 GHz and 333 kHz	2.4 GHz and 333 kHz
ESD tolerance	According to IEC 61000-4-2 Electrostatic discharge immunity test standard	According to IEC 61000-4-2 Electrostatic discharge immunity test standard
Operating & Charging temperature	+ 5 °C to + 40 °C at a relative humidity range of 15 % to 90 %, non-condensing	+ 5 °C to + 40 °C at a relative humidity range of 15 % to 90 %, non-condensing
Storage temperature for charger and Hearing Instrument	- 25 °C to + 5 °C, + 5 °C to + 35 °C at a relative humidity up to 90 %, non-condensing, > 35 °C to 70 °C at a water vapour pressure up to 50 hPa	- 25 °C to + 5 °C, + 5 °C to + 35 °C at a relative humidity up to 90 %, non-condensing, > 35 °C to 70 °C at a water vapour pressure up to 50 hPa

Patents pending

All specifications are subject to change without notice



Chargers



Premium charger C-1



Standard charger C-2