

# ReSound LiNX 3D™



LT88-DW

## Product Description

Model 88 Power Behind-the-Ear (PBTE) hearing aids support closed configurations.

The ReSound Smart Range C platform enables Surround Sound by ReSound.


This 5th generation, 2.4 GHz wireless product utilizes the Smart Range C platform for secure cloud connectivity, bringing an entirely new level to the relationship between hearing care professionals and their clients, called ReSound Assist. These Made for iPhone hearing aids also feature ear-to-ear communication along with a direct connection to the ReSound Smart 3D app.

ReSound LiNX 3D also supports the full line of ReSound wireless accessories.

The 88 BTE model comes standard with Push Button, Volume Control, Telecoil, and Direct Audio Input (DAI) functionality.

The ReSound LiNX 3D PBTE hearing aids are iSolate™ nanotech coated for optimum durability and meet the IP58 classification for ingress protection.

Fitting Range



Model	LT988-DW	LT788-DW	LT588-DW
<b>Device Configurations</b>			
Battery size	13		
Colors available	14		
<b>Audiological Features</b>			
WARP compression (WDRC) - number of channels	17	14	12
Binaural Directionality III	●	-	-
Spatial Sense	●	-	-
Binaural Directionality	-	●	-
Natural Directionality II	●	●	●
Directional Mix Processor	●	●	●
-Adjustable directional mix	●	-	-
Synchronized Soft Switching	●	●	-
Soft Switching	-	-	●
Autoscope Adaptive Directionality	●	-	-
Multiscope Adaptive Directionality	-	●	-
Adaptive Directionality	-	-	●
Binaural Environmental Optimizer II	●	-	-
Environmental Optimizer	-	●	-
NoiseTracker II	●	⊙	○
Expansion	●	⊙	○
Wind Guard	●	⊙	○
Sound Shaper	●	●	●
DFS Ultra II	●	●	●
-Music Mode	●	●	●
Synchronized Acceptance Manager	●	●	●
Low Frequency Boost	●	⊙	○
Amplification Strategy (WDRC/Semi-Linear/Linear)	●	●	⊙
Tinnitus Sound Generator	●	●	●
<b>Functional Features</b>			
Synchronized Push Button	●	●	●
Synchronized Volume Control	●	●	●
Smart Start	●	●	●
Phone Now	●	●	●
Comfort Phone	●	●	●
Ear to Ear Communication	●	●	●
Direct audio streaming (Made for iPhone)	●	●	●
ReSound TV Streamer 2, Remote Control 2, Phone Clip+, Micro Mic and Multi Mic	●	●	●
ReSound Control™ app (Phone Clip+ is required)	●	●	●
ReSound Smart 3D™ app	●	●	●
<b>ReSound Assist</b>			
Remote Fine Tuning	●	●	●
Remote Firmware Updates	●	●	●
<b>Fitting Features</b>			
Fitting Software Smart Fit™ 1.0 or higher	●	●	●
Fully Flexible Programs	4	4	4
Auto DFS	●	●	●
Onboard Analyzer II	●	●	●
Wireless Fitting with Airlink™2/ Noahlink Wireless	●	●	●

○ Basic  
⊙ Advanced  
● Ultimate



ReSound LiNX 3D is compatible with iPhone 7 Plus, iPhone 7, iPhone 6s Plus, iPhone 6s, iPhone 6 Plus, iPhone 6, iPhone SE, iPhone 5s, iPhone 5c, iPhone 5, iPad Pro (12.9-inch), iPad Pro (9.7-inch), iPad Air 2, iPad Air, iPad mini 4, iPad mini 3, iPad mini 2, iPad mini, iPad (4th generation), iPod touch (6th generation) and iPod touch (5th generation) using iOS 8.X or later. Apple, the Apple logo, iPhone, iPad Pro, iPad Air, iPad mini, iPad and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc.



# Technical Specifications


LT88-DW	
IEC 60118-0 2nd IEC 711 Ear simulator	IEC 60118-0 3rd IEC 60118-7 ANSI S3.22 2cc coupler

Reference test gain (60 dB SPL input)	1600 Hz/HFA	54	51	dB
Full-on gain (50 dB SPL input)	Max. 1600 Hz/HFA	74 67	67 63	dB
Maximum output (90 dB SPL input)	Max. 1600 Hz/HFA	140 134	132 128	dB SPL
Total harmonic distortion	500 Hz 800 Hz 1600 Hz	0.5 1.1 0.4	0.5 0.5 0.3	%
Telecoil sensitivity (1 mA/m input)	Max.	102		dB SPL
HFA - SPLIV @ 31.6 mA/m (ANSI)	HFA		111	
Full-on telecoil sensitivity @ 1mA/m	1600 Hz/HFA	95	91	
Equivalent input noise		23	22	dB SPL
Frequency range (DIN 45605/ANSI)		100-6652	100-6020	Hz
Current drain		1.2	1.4	mA


Data in accordance with IEC60118-0 Edition3.0  
2015-06, IEC60118-7 and ANSI S3.22-2009, supply  
Voltage 1.3V

Patents pending

Maximum Output (OSPL 90)



Maximum Output (OSPL 90)




Notes:  
O.E.S. = Occluded Ear Simulator  
2cc = 2 cm<sup>3</sup> coupler  
Pi = Acoustic input signal


Basic settings:  
Full-on Gain, Reference Test Gain  
MPO = Maximum Power Output  
Maximum Band Width

All specifications are subject to change without notice

Full-On and Reference Test Gain




Full-On and Reference Test Gain




Measured according to IEC60118-0 Edition3.0 2015-06 at 1.3 V, impedance 6.2 ohms and 23°C on 2cc coupler. Resp. on 2cc according to IEC60118-7 Second edition 2005-10 and ANSI/ASA S3.22-2009 (HFA average calculated at 1000 Hz, 1600 Hz and 2500 Hz; 0 dB SPL sound pressure equals 20µPa). All measurements without DSP features activated unless indicated otherwise  
Measurement on O.E.S according to IEC711 1981 According to IEC60118-0 Edition 2 1983 and amendment 1 1994

Input/Output Response



Full-On Telecoil Response  
Input level 10 mA/m



400628000GB-16.12-Rev.C

**ReSound A/S**  
Lautrupbjerg 7  
DK-2750 Ballerup, Denmark  
Tel.: +45 45 75 11 11  
resound.com

**United Kingdom**  
GN ReSound Ltd.  
Kirtlington Business Centre  
Portway  
Kirtlington  
Oxon OX5 3JA  
Tel.: +44 1869 352 800  
resound.com

**Australia**  
GN ReSound Pty. Ltd.  
Unit R1 Regent Park Estate  
391 Park Road  
Regent Park NSW 2143  
Tel.: 02 9743 9707  
Free call number: 1800 658 955  
resound.com

**New Zealand**  
GN ReSound (NZ) Ltd.  
Ground Floor, North Entrance  
4 Fred Thomas Drive  
Takapuna  
Auckland, 0622  
Tel.: (free) 0800 900 126  
resound.com

